




**LED converter 350 mA, DALI dimmable (digital)**  
 Article no. 17684000



**Tender**  
 LED converter 350 mA, DALI dimmable (digital), Rectangular. Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7 W, Dimmable: Yes, Type of dimming: DALI-2/PUSH.

**Product Benefits**

We guarantee: No afterglow of the LEDs. A weak afterglow of the LED lights in the switched-off state is an undesirable, unacceptable effect. With our new LED converter, this is eliminated. This reduces troubleshooting as well as installation efforts and offers optimal operational reliability. The converter is available in three versions and additionally already integrated in the BB sets.

Article data	
Article no.	17684000
GTIN	4251433951186
Short description	LED converter 350 mA, DALI dimmable (digital)
Material	Plastic
Shape	Rectangular
Length	130 mm
Width	42 mm
Height	22 mm
Scope of delivery	Plug&Play-Ausgangsleitung, Länge 110 mm
Weight	0.106 kg
stamp	ENEC 05, EL
Conformance	CE


**LED converter 350 mA, DALI dimmable (digital)**

Article no. 17684000

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	47 Hz
Frequency max	63 Hz
DC nominal voltage min	186 V
DC nominal voltage max	250 V
Protection class	II
Degree of protection	IP20
Power	2.8 W
Power max.	7 W
Output_ripple_current	4
Starting current	1 A, 15,2 $\mu$ s
Suitable for emergency lighting	No
measure point (tc)	70 °C
Version	Plug&Play
Power factor	0.97
max. no. lights on B10 A	157
max. no. lights on B16 A	250
max. no. lights on C16 A	425
max. no. lights on C10 A	250
Output voltage max	20.00 V
Output voltage min.	8.00 V
Flicker value Pst LM	1.00
Control	DALI-2/PUSH
Connection type-primary	Plug-in connection
Connection type-secondary	Plug clamp
Number of poles	2
Flicker-free	Yes
Environment temperature (ta)	-20°C up to +50°C
Measure point (tc)	max. +70 °C
Average nominal lifespan	50000 h
Output current	350 mA
Safety devices against thermal overload	yes

Packing data	
Gross weight	0.106 kg
Length of packaging	60 mm
Packaging width	27 mm
Packaging height	150 mm
Disposal at end of life	<p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p>