


134 CG-S




Escape sign luminaire Hotel



134 CG-S




- Safety luminaire with three-sided light outlet
- For horizontal and vertical wall or ceiling mounting
- Low construction height means especially suitable for areas with low ceilings
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditure with STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit

134 CG-S



Viewing distance	12 m
Luminous flux Φ_E/Φ_N at the end of rated operating time	75 %
Housing material	Aluminium/Plastic cover
Weight incl. panel	0.70 kg
Housing colour	White
Type of mounting	Wall or ceiling mounting
Connection terminals	Loop terminals 3 x 2.5 mm ²
Connection voltage	220 – 240 V AC, 50/60 Hz 176 – 275 V DC
Current consumption - battery operation (220 V)	20 mA
Power consumption mains operation	8 VA
Permissible ambient temperature	-10 °C to +40 °C
Light source	4 W/T16

Ordering details

Type	Scope of supply	Order No.
134 CG-S	Luminaire with CEWA GUARD monitoring and 20-digit address switch, without covers	40071341874
Cover PL	Cover with pictogram acc. to ISO 7010 	40071354290
Cover PR	Cover with pictogram acc. to ISO 7010 	40071354291
Cover PU	Cover with pictogram acc. to ISO 7010 	40071354292
Cover	Opaque cover	40071345562
Blind cover		40071345563


Each luminaire requires 3 covers

Accessories

Type	Order No.
Wire guard	40071348370

Planning help for 134 CG-S for E = 1.0 lx (0.5 lx)

Measuring level 0.02 m, maintenance factor MF = 80 %, battery operation, distances in m

Mounting height [m]	Types of mounting	Diagram	
		L1 	L2 
2.0	Wall mounting	2.6 (3.3)	6.6 (7.8)
2.5		2.4 (3.3)	6.6 (8.4)
3.0		2.3 (3.2)	6.4 (8.6)