



Product Features

"BasicLine splice box, extensible, 19"/1U, 6xLC-D, OS2 APC, green"

- sheet steel housing, powder coated
- labelled ports
- with slide-in unit
- can be tilted downwards when opened
- front quick release (push-pull)
- splice cassette for holding 12 or 24 pigtails
- inserted crimp splice holder
- prepared with pigtails inserted in bundle of 12 incl. 6 x LC-D ceramic couplings
- 12 LC-fibre pigtails E9/125 µm, 2 m, SM PC, grade B
- with test protocol for all fibres incl. serial number
- mounted blind stops by less than 12 ports
- 2 x PG13,5/M20 - cable glands in the back (each 2 x right/left)
- 1 x PG13.5 gland in scope of delivery
- black (similar to RAL 9005)

Features

General	
Surface	steel sheet, powder-coated
Classification	OS2 APC (8°)
Protection class IP	20
Halogen Free	Yes
Statistical goods number	85367000
Country of manufacture	DE
GTIN (EAN)	4043921667002
ETIM class	STANDARD
Mounting types	
(19-inch)-installation, 1 rack unit	Yes
Dimensions/Weights without packaging	
Length mm	482
Width mm	245
Height mm	44
Net weight piece kg	1,213
Certifications	
RoHS conform	Yes

BL-Spleissbox 6xLC-D OS2 APC grün

Article no.: 2280304060

Color: black (similar RAL 9005)

Logistics Information	
Packaging	box
Packaging unit Quantity	1
Packaging unit Weight kg	1,349
Packaging unit Width mm	305
Packaging unit Height mm	60
Packaging unit Depth mm	510
References	
Accessories	228040002, 228040102, 228040302, 228060000, 228060100, 228060300, 228070000, 228070100, 228070200, 228070312