

## Han EE module, crimp female



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Part number        | 09 14 008 3101                                                                |
| Specification      | Han EE module, crimp female                                                   |
| HARTING eCatalogue | <a href="https://harting.com/09140083101">https://harting.com/09140083101</a> |

### Identification

|                    |                |
|--------------------|----------------|
| Category           | Modules        |
| Series             | Han-Modular®   |
| Type of module     | Han® EE module |
| Size of the module | Single module  |

### Version

|                    |                                         |
|--------------------|-----------------------------------------|
| Termination method | Crimp termination                       |
| Gender             | Female                                  |
| Number of contacts | 8                                       |
| Details            | Please order crimp contacts separately. |

### Technical characteristics

|                          |                            |
|--------------------------|----------------------------|
| Conductor cross-section  | 0.14 ... 4 mm <sup>2</sup> |
| Wire outer diameter      | ≤4.8 mm                    |
| Rated current            | 16 A                       |
| Rated voltage            | 400 V                      |
| Rated impulse voltage    | 6 kV                       |
| Pollution degree         | 3                          |
| Rated voltage acc. to UL | 600 V                      |
| Insulation resistance    | >10 <sup>10</sup> Ω        |
| Limiting temperature     | -40 ... +125 °C            |
| Mating cycles            | ≥10,000                    |



**Pushing Performance**  
Since 1945

## Technical characteristics

|                           |                                         |
|---------------------------|-----------------------------------------|
| Note on the mating cycles | Mating cycles with other HMC components |
|---------------------------|-----------------------------------------|

## Material properties

|                                           |                                     |
|-------------------------------------------|-------------------------------------|
| Material (insert)                         | Polycarbonate (PC)                  |
| Colour (insert)                           | RAL 7032 (pebble grey)              |
| Material flammability class acc. to UL 94 | V-0                                 |
| RoHS                                      | compliant                           |
| ELV status                                | compliant                           |
| China RoHS                                | e                                   |
| REACH Annex XVII substances               | Not contained                       |
| REACH ANNEX XIV substances                | Not contained                       |
| REACH SVHC substances                     | Not contained                       |
| California Proposition 65 substances      | Not contained                       |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08) + A1 (2023-10) |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3)        |

## Specifications and approvals

|                |                                                                                     |
|----------------|-------------------------------------------------------------------------------------|
| Specifications | IEC 60664-1<br>IEC 61984<br>IEC 61373 Category 2                                    |
| UL / CSA       | UL 1977 ECBT2.E235076<br>UL 2237 PVVA2.E318390<br>CSA-C22.2 No. 182.3 PVVA8.E318390 |
| Approvals      | DNV GL                                                                              |

## Commercial data

|                                |                                                           |
|--------------------------------|-----------------------------------------------------------|
| Packaging size                 | 2                                                         |
| Net weight                     | 2 g                                                       |
| Country of origin              | Germany                                                   |
| European customs tariff number | 85389099                                                  |
| GTIN                           | 5713140020719                                             |
| eCl@ss                         | 27440217 Module for industrial connectors (power/signals) |
| ETIM                           | EC000438                                                  |
| UNSPSC 24.0                    | 39121552                                                  |