




**BREENA-R LED recessed spot set, trailing-edge phase dimmable**

Article no. 39141153


**Tender**

LED recessed spot set, trailing-edge phase dimmable, Round. Toolless ceiling installation by installation springs. Ceiling cut-out Ø 68 mm, Installation depth 42 mm, Outer diameter 88 mm, Weight 0,301 kg, Reflector silver with rotationssymmetrical, deep, wide distributed light intensity. Cover glass transparent Luminous flux 730 lm, Power 1 x 6 W, Light colour warm white, Correlated color temperature (CCT) 3.000 K, Colour rendering index CRI > 80, Housing material: Zinc casting / Aluminium casting / Aluminium / Glass / Plastic, Colour: nickel matt, Permissible ambient temperature (ta): -20 °C up to +25 °C, Protection class (EN 61140): II, Degree of protection (DIN EN 60529): IP20. With electronic driver, Trailing-edge phase dimmable.

**Product Benefits**

- LED recessed spotlight in round design made of solid cast zinc and cast aluminum with 6 W LED module (3,000 K) and dimmable converter (phase cut-off).
- Ceiling cut-out 68 mm, diameter 88 mm, installation depth 50 mm, IP20.
- Pivoting range 25°.
- Without visible snap ring.
- Classic, formally restrained design.
- Also available in the same look in GX5.3 or GU10 versions and as a switchable set.


**BREENA-R LED recessed spot set, trailing-edge phase dimmable**

Article no. 39141153

| Article data           |                                                                |
|------------------------|----------------------------------------------------------------|
| Article no.            | 39141153                                                       |
| GTIN                   | 4251433950776                                                  |
| Series name            | BREENA-R                                                       |
| Short description      | LED recessed spot set, trailing-edge phase dimmable            |
| Material               | Zinc casting / Aluminium casting / Aluminium / Glass / Plastic |
| Colour                 | nickel matt                                                    |
| Type of surface        | Matt                                                           |
| Shape                  | Round                                                          |
| Outer diameter         | 88 mm                                                          |
| Built-in diameter min. | 68 mm                                                          |
| Built-in diameter max. | 68 mm                                                          |
| Installation depth     | 42 mm                                                          |
| Hight                  | 5 mm                                                           |
| Weight                 | 0.301 kg                                                       |
| D licence plate        | No                                                             |
| Conformance            | CE, UKCA                                                       |

| Lighting technology          |           |
|------------------------------|-----------|
| Colour temperature           | 3.000 K   |
| Light colour                 | white     |
| Light output                 | Direct    |
| Luminous flux                | 730 lm    |
| System efficiency            | 122 lm/W  |
| Colour rendering             | CRI > 80  |
| Reflector                    | Faceted   |
| Reflector colour             | silver    |
| Beam angle                   | 38°       |
| Light sharing                | Symmetric |
| Adjustable color temperature | No        |

| Operating technology of the light source |                                                                                                                                                          |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Article No. of used light source         | 12924383                                                                                                                                                 |
| Hight                                    | 32 mm                                                                                                                                                    |
| Outer diameter                           | 51 mm                                                                                                                                                    |
| Lamp holder                              | Plug&Play                                                                                                                                                |
| Power                                    | 6 W                                                                                                                                                      |
| Voltage type                             | DC                                                                                                                                                       |
| Current                                  | 350 mA                                                                                                                                                   |
| Lamp                                     | LED                                                                                                                                                      |
| Protection class                         | III                                                                                                                                                      |
| Degree of protection                     | IP20                                                                                                                                                     |
| Energy efficiency class                  | D                                                                                                                                                        |
| Bulb change possible                     | The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person. |


**BREENA-R LED recessed spot set, trailing-edge phase dimmable**

Article no. 39141153

| Operating technology of driver |                     |
|--------------------------------|---------------------|
| Article No. of used driver     | 17663000            |
| Length                         | 110 mm              |
| Width                          | 50 mm               |
| Hight                          | 19 mm               |
| AC nominal voltage min         | 198 V               |
| AC nominal voltage max         | 264 V               |
| Frequency max                  | 63 Hz               |
| Dimmable                       | Yes                 |
| Control                        | Trailing-edge phase |
| Starting current               | 1 A, 15,2 µs        |
| Power                          | 2.8 W               |
| Power                          | 7 W                 |
| Output current up to           | 350 mA              |
| Degree of protection           | IP20                |
| Protection class               | II                  |
| Flicker-free                   | Yes                 |
| stamp                          | ENEC 05             |

| Mounting technology         |                                           |
|-----------------------------|-------------------------------------------|
| Mounting method             | Recessed mounting                         |
| Place of installation       | Ceiling-mounted                           |
| Adjustability               | Pivoted                                   |
| Swivel angle                | 20°                                       |
| Max. ceiling thickness      | 15 mm                                     |
| Further references          | No cover with thermal insulation material |
| Cover                       | Glass transparent                         |
| Circlip                     | Without circlip                           |
| Suitable for through-wiring | Yes, with optional accessories            |

| Packing data            |                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Gross weight            | 0.358 kg                                                                                                                                                                                                                                                                                                                                                                       |
| Length of packaging     | 100 mm                                                                                                                                                                                                                                                                                                                                                                         |
| Packaging width         | 100 mm                                                                                                                                                                                                                                                                                                                                                                         |
| Packaging hight         | 100 mm                                                                                                                                                                                                                                                                                                                                                                         |
| Disposal at end of life | <p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p> |

**BREENA-R LED recessed spot set, trailing-edge phase dimmable**  
Article no. 39141153**Optional accessories**

Article no.: 81204150

Reducing ring D 110 mm, for luminaire cut-out size 68 mm

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_81204150\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_81204150_2021_DE.pdf)

Article no.: 81205150

Reducing ring D 130 mm, for luminaire cut-out size 68 mm

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_81205150\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_81205150_2021_DE.pdf)

Article no.: 81206150

Reducing ring D 145 mm, for luminaire cut-out size 68 mm

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_81206150\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_81206150_2021_DE.pdf)

Article no.: 83330000

Connection box 230 V AC, 3-pole

Dimensions: 85 mm x 35 mm x 30 mm

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_83330000\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_83330000_2021_DE.pdf)

Article no.: 5327

Leaf spring set (2 pieces)

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_00532700\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_00532700_2021_DE.pdf)