





## OGDAN Recessed downlight, IP65, GX5,3

Article no. 2062.25



### Tender

Recessed downlight, IP65, GX5,3, nickel matt, Round. In a compact design, for installation in tool-less rapid assembly systems. Lamp holder: GX5.3, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Cast iron / Glass, Degree of protection: (DIN EN 60529) IP65, Protection class: (DIN EN 61140) III, Voltage: 12 V, Power: 13 W, Amount of light sources / fittings: 1 piece, Light colour: white, Adjustability: Not adjustable, without control gear, Dimmable: Depending on type of control gear, Type of dimming: Depending on driver.

### Product Benefits

- Einbaudownlight in runder Bauform aus Guss für LED-Retrofit-Lampen mit Sockel GX5,3.
- Deckenausschnitt 68 mm, Durchmesser 82 mm, Einbautiefe 80 mm, IP65. (bei Einbau in geschlossenen Decken).
- Ausführung: ohne Sprengring.
- Klassische, formal zurückgenommene Formgebung.
- In gleicher Optik auch als GU10-Ausführung, als schaltbares und dimmbares Set (Phasenabschnitt) lieferbar.


**OGDAN Recessed downlight, IP65, GX5,3**

Article no. 2062.25

| Article data           |                                 |
|------------------------|---------------------------------|
| Article no.            | 2062.25                         |
| GTIN                   | 4250047730347                   |
| Series name            | OGDAN                           |
| Short description      | Recessed downlight, IP65, GX5,3 |
| Material               | Cast iron / Glass               |
| Colour                 | nickel matt                     |
| Type of surface        | Matt                            |
| Shape                  | Round                           |
| Outer diameter         | 82 mm                           |
| Built-in diameter min. | 65 mm                           |
| Built-in diameter max. | 68 mm                           |
| Installation depth     | 80 mm                           |
| Hight                  | 8 mm                            |
| Weight                 | 0.1 kg                          |
| D licence plate        | No                              |
| Conformance            | CE, UKCA                        |

| Operating technology of the luminaire |                                   |
|---------------------------------------|-----------------------------------|
| System output                         | 13 W                              |
| Voltage type                          | AC/DC                             |
| AC nominal voltage max                | 12 V                              |
| Frequency max                         | 50 Hz                             |
| Lamp                                  | For LED-retrofill lamp            |
| Lamp holder                           | GX5.3                             |
| Protection class                      | III                               |
| Protection class on the ceiling side  | IP20                              |
| Degree of protection                  | IP65                              |
| Dimmable                              | Depending on type of control gear |
| Control                               | Depending on driver               |
| Bulb change possible                  | Yes                               |
| Energy efficiency class               | not required                      |

| Mounting technology    |                                                                     |
|------------------------|---------------------------------------------------------------------|
| Mounting method        | Recessed mounting                                                   |
| Place of installation  | Ceiling-mounted                                                     |
| Adjustability          | Not adjustable                                                      |
| Max. ceiling thickness | 13 mm                                                               |
| Further references     | No mounting box No cover with thermal insulation material Smarthome |
| Cover                  | Glass, satinised                                                    |
| Circlip                | Without circlip                                                     |

| Packing data            |                                                                                                                                                                                                                                                                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Gross weight            | 0.13 kg                                                                                                                                                                                                                                                                                                                                                                        |
| Length of packaging     | 85 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Packaging width         | 85 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Packaging hight         | 68 mm                                                                                                                                                                                                                                                                                                                                                                          |
| Disposal at end of life | <p>This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately.</p> <p>By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.</p> |


**OGDAN Recessed downlight, IP65, GX5,3**

Article no. 2062.25

| Compatible LED-modu- |        |            |                                                             |                  |               |         |       |
|----------------------|--------|------------|-------------------------------------------------------------|------------------|---------------|---------|-------|
| Article no.          | Power  | Beam angle | Colour temperature                                          | Colour rendering | Luminous flux | Input   | Hight |
| 12925003             | 3 W    | 38°        | 2.700 K                                                     | CRI > 80         | 290 lm        | 350 mA  | 40 mm |
| 12926003             | 3 W    | 38°        | 3.000 K                                                     | CRI > 80         | 310 lm        | 350 mA  | 40 mm |
| 12925004             | 3 W    | 38°        | 4.000 K                                                     | CRI > 80         | 340 lm        | 350 mA  | 40 mm |
| 12923383             | 6 W    | 38°        | 2.700 K                                                     | CRI > 80         | 740 lm        | 350 mA  | 32 mm |
| 12923603             | 6 W    | 60°        | 2.700 K                                                     | CRI > 80         | 720 lm        | 350 mA  | 32 mm |
| 12927383             | 6 W    | 38°        | 2.700 K                                                     | CRI > 90         | 600 lm        | 350 mA  | 32 mm |
| 12924383             | 6 W    | 38°        | 3.000 K                                                     | CRI > 80         | 730 lm        | 350 mA  | 32 mm |
| 12924603             | 6 W    | 60°        | 3.000 K                                                     | CRI > 80         | 770 lm        | 350 mA  | 32 mm |
| 12928383             | 6 W    | 38°        | 3.000 K                                                     | CRI > 90         | 680 lm        | 350 mA  | 32 mm |
| 12924384             | 6 W    | 38°        | 3.500 K                                                     | CRI > 80         | 730 lm        | 350 mA  | 32 mm |
| 12924604             | 6 W    | 60°        | 3.500 K                                                     | CRI > 80         | 770 lm        | 350 mA  | 32 mm |
| 12928384             | 6 W    | 38°        | 3.500 K                                                     | CRI > 90         | 680 lm        | 350 mA  | 32 mm |
| 12923384             | 6 W    | 38°        | 4.000 K                                                     | CRI > 80         | 770 lm        | 350 mA  | 32 mm |
| 12923604             | 6 W    | 60°        | 4.000 K                                                     | CRI > 80         | 790 lm        | 350 mA  | 32 mm |
| 12927384             | 6 W    | 38°        | 4.000 K                                                     | CRI > 90         | 720 lm        | 350 mA  | 32 mm |
| 12920183             | 6 W    | 18°        | 3.000 K                                                     | CRI > 80         | 740 lm        | 350 mA  | 31 mm |
| 12920243             | 6 W    | 24°        | 3.000 K                                                     | CRI > 80         | 760 lm        | 350 mA  | 31 mm |
| 12920003             | 6 W    | 38°        | 3.000 K                                                     | CRI > 80         | 780 lm        | 350 mA  | 31 mm |
| 12920603             | 6 W    | 60°        | 3.000 K                                                     | CRI > 80         | 760 lm        | 350 mA  | 31 mm |
| 12920184             | 6 W    | 18°        | 4.000 K                                                     | CRI > 80         | 780 lm        | 350 mA  | 31 mm |
| 12920244             | 6 W    | 24°        | 4.000 K                                                     | CRI > 80         | 790 lm        | 350 mA  | 31 mm |
| 12920004             | 6 W    | 38°        | 4.000 K                                                     | CRI > 80         | 810 lm        | 350 mA  | 31 mm |
| 12920604             | 6 W    | 60°        | 4.000 K                                                     | CRI > 80         | 780 lm        | 350 mA  | 31 mm |
| 12963383             | 6 W    | 38°        | 3.000 K - 1.800 K                                           | CRI > 90         | 460 lm        | 350 mA  | 32 mm |
| 12963603             | 6 W    | 60°        | 3.000 K - 1.800 K                                           | CRI > 90         | 460 lm        | 350 mA  | 32 mm |
| 12953003             | 12 W   | 38°        | 2.700 K                                                     | CRI > 80         | 1,130 lm      | 350 mA  | 70 mm |
| 12954003             | 12 W   | 38°        | 3.000 K                                                     | CRI > 80         | 1,360 lm      | 350 mA  | 70 mm |
| 12954004             | 12 W   | 38°        | 3.500 K                                                     | CRI > 80         | 1,290 lm      | 350 mA  | 70 mm |
| 12953004             | 12 W   | 38°        | 4.000 K                                                     | CRI > 80         | 1,300 lm      | 350 mA  | 70 mm |
| 12965003             | 12 W   | 38°        | 3.000 K - 1.800 K                                           | CRI > 90         | 930 lm        | 350 mA  | 70 mm |
| 12983003             | 12.5 W | 38°        | 3.000 K                                                     | CRI > 97         | 920 lm        | 350 mA  | 95 mm |
| 12823003             | 8 W    | 60°        | 2.850 K                                                     | CRI > 90         | 900 lm        | 24.00 V | 52 mm |
| 12845604             | 8 W    | 60°        | 2.700 K - 6.500 K                                           | CRI > 90         | 659 lm        | 24.00 V | 52 mm |
| 18438002             | 8 W    | 60°        | RGB + WW                                                    | CRI > 90         | 400 lm        | 24.00 V | 52 mm |
| 12929503             | 6.3 W  | 50°        | 2.700 K / 3.000 K / 4.000 K                                 | CRI > 80         | 1,023 lm      | 350 mA  | 34 mm |
| 12930503             | 5.9 W  | 50°        | 2.700 K / 3.000 K / 4.000 K                                 | CRI > 90         | 810 lm        | 350 mA  | 34 mm |
| 12933553             | 6 W    | 55°        | 2.700 K / 3.000 K / 4.000 K + dim-2warm (3.000 K - 2.200 K) | CRI > 90         | 730 lm        | 350 mA  | 32 mm |

**OGDAN Recessed downlight, IP65, GX5,3**

Article no. 2062.25

**Optional accessories**

Article no.: 5366

Bracket with GX5.3 socket, with strain relief

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_00536600\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_00536600_2021_DE.pdf)

Article no.: 5358

Bracket with socket GZ10, with strain relief

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_00535800\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_00535800_2021_DE.pdf)

Article no.: 81201150

Reducing ring D 110 mm, for luminaire cut-out size 68 mm

Dimensions: 110 mm

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_81201150\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_81201150_2021_DE.pdf)

Article no.: 81202150

Reducing ring D 130 mm, for luminaire cut-out size 68 mm

Dimensions: 130 mm

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_81202150\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_81202150_2021_DE.pdf)

Article no.: 81203150

Reducing ring D 145 mm, for luminaire cut-out size 68 mm

Dimensions: 145 mm

[https://www.brumberg.com/fileadmin/products/Datenblatt\\_81203150\\_2021\\_DE.pdf](https://www.brumberg.com/fileadmin/products/Datenblatt_81203150_2021_DE.pdf)