





SUNNY MIDI Surface-mounted LED ceiling downlight, trailing edge dimmable, 440 mm

Article no. 12209073


Tender

Surface-mounted LED ceiling downlight, trailing edge dimmable, 440 mm, Round. Luminaire diameter 440.0 mm, Height 50.0 mm Weight 2.342 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, opal Luminous flux 3.750 - 4.165 lm, UGR < 25, Power 1 x 40 W, Light colour warm white to daylight white, Correlated color temprature (CCT) 3.000 - 6.000 K, Colour rendering index CRI > 80, Rated life time L70/B50 at 25 °C: 50.000 h, Housing material: Aluminium / Steel / Polystyrene, Colour: white matt, Permissible ambient temperature (ta): -20 °C up to +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP20, shock resistance according to IEC62262: IK04 .With electronic driver, Trailing-edge phase dimmable.

Product Benefits

- Standard indirect component in white, can be retrofitted individually as accessories available in amber, blue and red.
- Easy installation due to bayonet mounting and arrestor cable.
- Luminaire can be easily removed without screws thanks to separate mounting plate.
- Three sizes: 330 mm, 440 mm or 550 mm.
- Three on-site adjustable light colors: 3,000 K, 4,000 K and 6,000 K.
- As an additional function: light color adjustable on the switch side via bottom switch function.
- Also available as pendant version (accessory: pendant set 1,500 mm).
- Dimmable as standard via phase cut-off or DALI (size: 440 mm and 550mm).


SUNNY MIDI Surface-mounted LED ceiling downlight, trailing edge dimmable, 440 mm

Article no. 12209073

Article data	
Article no.	12209073
GTIN	4251433930440
Series name	SUNNY MIDI
Short description	Surface-mounted LED ceiling downlight, trailing edge dimmable, 440 mm
Material	Aluminium / Steel / Polystyrene
Colour	white matt
Type of surface	Matt
Shape	Round
Outer diameter	440 mm
Height	50 mm
Scope of delivery	incl. converter for connection to 230 V mains voltage, dimmable and incl. adjustable color temperature to 3,000 K, 4,000 K or 6,000 K (switchover on the housing or via wall-mounted switch via bottom switch function). Optional accessories: color ring set for the indirect component in the colors red, blue and amber, as well as a pendant set 1,500 mm.
Weight	2.342 kg
D licence plate	No
Conformance	CE, UKCA

Lighting technology	
Colour temperature	3.000 K / 4.000 K / 6.000 K
Light colour	white
Color Temperature 1	3,000 K
Color Temperature 2	4,000 K
Color Temperature 3	6,000 K
Light output	Direct/Indirect
Luminous flux	3,750 - 4,165 lm
Luminous flux 1	3,750 lm
Luminous flux 2	4,165 lm
Luminous flux 3	3,750 lm
System efficiency	104 lm/W
Colour rendering	CRI > 80
Reflector	Without
Beam angle	110°
Glare evaluation	UGR < 25
Light sharing	Symmetric
Adjustable color temperature	Stages

Operating technology of the luminaire	
System output	40 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	I
Degree of protection	IP20
Dimmable	Yes
Control	Trailing-edge phase
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Rated life time L70/B50 at 25 °C	50,000 h
Energy efficiency class	not required


SUNNY MIDI Surface-mounted LED ceiling downlight, trailing edge dimmable, 440 mm

Article no. 12209073

Mounting technology	
Mounting method	Surface mounting
Place of installation	Ceiling-mounted
Adjustability	Not adjustable
Impact resistance	IK04
Cover	Plastic, opal

Packing data	
Gross weight	2.719 kg
Length of packaging	480 mm
Packaging width	475 mm
Packaging height	55 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.

Optional accessories	
Article no.: 81020906 Color ring set for SUNNY surface-mounted luminaire	
	https://www.brumberg.com/fileadmin/products/Datenblatt_81020906_2021_DE.pdf
Article no.: 81020908 Color ring set for SUNNY surface-mounted luminaire	
	https://www.brumberg.com/fileadmin/products/Datenblatt_81020908_2021_DE.pdf
Article no.: 81020909 Color ring set for SUNNY surface-mounted luminaire	
	https://www.brumberg.com/fileadmin/products/Datenblatt_81020909_2021_DE.pdf
Article no.: 81018070 Pendant set for surface-mounted downlight 12208073 / 12209073	
Dimensions: 150 mm x 26 mm	
	https://www.brumberg.com/fileadmin/products/Datenblatt_81018070_2021_DE.pdf
Article no.: 81018080 Pendant set for surface-mounted downlight 12208073 / 12209073	
Dimensions: 150 mm x 26 mm	
	https://www.brumberg.com/fileadmin/products/Datenblatt_81018080_2021_DE.pdf