






EYE LED surface-mounted wall light, IP65, 3CCT, switchable
Article no. 10137183



Tender
LED surface-mounted wall light, IP65, 3CCT, switchable, Round. Luminaire diameter 251.0 mm, Weight 1.259 kg, with rotationssymmetrical, deep, wide distributed light intensity. Cover plastic, opal. Luminous flux 900 lm, Power 1 x 18 W, Light colour warm white to daylight white, Correlated color temperature (CCT) 3.000 - 5.700 K, Colour rendering index CRI > 80, Housing material: Aluminium / Plastic, Colour: black structure, Permissible ambient temperature (ta): -20 °C up to +25 °C, Protection class (EN 61140): I, Degree of protection (DIN EN 60529): IP65, shock resistance according to IEC62262: IK08. With electronic driver, on/off switchable.

Article data	
Article no.	10137183
GTIN	4251433971863
Series name	EYE
Short description	LED surface-mounted wall light, IP65, 3CCT, switchable
Material	Aluminium / Plastic
Colour	black structure
Type of surface	Structure
Shape	Round
Outer diameter	251 mm
Width	76 mm
Scope of delivery	incl. converter for connection to 230 V mains voltage, switchable
Weight	1.259 kg
D licence plate	No
Conformance	CE, UKCA


EYE LED surface-mounted wall light, IP65, 3CCT, switchable

Article no. 10137183

Lighting technology	
Colour temperature	3.000 K / 4.000 K / 5.700 K
Light colour	white
Color Temperature 1	3,000 K
Light output	Direct/Indirect
Luminous flux	900 lm
Luminous flux 1	900 lm
System efficiency	50 lm/W
Colour rendering	CRI > 80
Luminaire optics	Cover satin
Reflector	Without
Beam angle	120°
Light sharing	Symmetric
Adjustable color temperature	Stages

Operating technology of the luminaire	
System output	18 W
Voltage type	AC
AC nominal voltage max	230 V
Frequency max	50 Hz
Lamp	LED
Lamp holder	Without fitting
Protection class	I
Degree of protection	IP65
Dimmable	No
Control	on/off
Bulb change possible	The light source of this luminaire may only be replaced by the manufacturer or a service technician commissioned by him or a similarly qualified person.
Energy efficiency class	not required

Mounting technology	
Mounting method	Surface mounting
Place of installation	Wall-mounted
Adjustability	Not adjustable
Impact resistance	IK08
Cover	Plastic, opal
Suitable for through-wiring	Yes

Packing data	
Gross weight	1.489 kg
Length of packaging	285 mm
Packaging width	280 mm
Packaging height	100 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.