





LED converter 350 mA, on/off switchable
Article no. 17621010



Tender
LED converter 350 mA, on/off switchable, white, Rectangular. Material: Plastic, Degree of protection: (DIN EN 60529) IP20, Protection class: (DIN EN 61140) II, Voltage: 230V AC 50Hz, Power: 21 W, Dimmable: No, Type of dimming: on/off.

Article data	
Article no.	17621010
GTIN	4251433918509
Short description	LED converter 350 mA, on/off switchable
Material	Plastic
Colour	white
Shape	Rectangular
Length	128 mm
Width	50 mm
Hight	13 mm
Weight	0.068 kg
stamp	ENEC 17
Conformance	CE


LED converter 350 mA, on/off switchable

Article no. 17621010

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	47 Hz
Frequency max	63 Hz
Protection class	II
Degree of protection	IP20
Power min.	1 W
Power max.	21 W
Output_ripple_current	50
Starting current	8 A, 500 ms
Suitable for emergency lighting	No
Ambient temperature	-20 up to 45 °C
measure point (tc)	110 °C
Version	without packaging
Power factor	0.55
max. no. lights on B10 A	11
max. no. lights on B16 A	18
max. no. lights on C16 A	39
max. no. lights on C10 A	24
Control	on/off
Number of poles	2
Flicker-free	Yes
Environment temperature (ta)	-20 °C bis +45 °C
Measure point (tc)	max. +70 °C
Average nominal lifespan	30,000 h
Output current up to	350 mA

Packing data	
Gross weight	0.087 kg
Length of packaging	60 mm
Packaging width	27 mm
Packaging height	150 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.