




LED converter 700 mA, trailing-edge phase dimmable
Article no. 17746020



Tender	
LED converter 700 mA, trailing-edge phase dimmable, white, Rectangular. Material: Plastic, Degree of protection: (DIN EN 60529) IP20, Protection class: (DIN EN 61140) II, Voltage: 230V AC 50Hz , Power: 20 W, Dimmable: Yes, Type of dimming: Trailing-edge phase.	

Article data	
Article no.	17746020
GTIN	4251433924081
Short description	LED converter 700 mA, trailing-edge phase dimmable
Material	Plastic
Colour	white
Shape	Rectangular
Length	110.5 mm
Width	52 mm
Hight	22 mm
Scope of delivery	Plug&Play output cable, length 110 mm and connection box
Weight	0.153 kg
stamp	ENEC 05
Conformance	CE


LED converter 700 mA, trailing-edge phase dimmable

Article no. 17746020

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	47 Hz
Frequency max	63 Hz
Protection class	II
Degree of protection	IP20
Power	11.2 W
Power max.	20 W
Output_ripple_current	20
Starting current	2 A, 50 µs
Suitable for emergency lighting	No
Ambient temperature	-25 up to 45 °C
measure point (tc)	75 °C
Version	Plug & Play + Connection Box
Power factor	0.95
max. no. lights on B16 A	50
Flicker value Pst LM	1.00
Control	Trailing-edge phase
Number of poles	2
Environment temperature (ta)	-25 °C bis +45 °C
Measure point (tc)	max. +85 °C
Output current up to	700 mA

Packing data	
Gross weight	0.21 kg
Length of packaging	100 mm
Packaging width	100 mm
Packaging height	100 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.