




LED converter 700 mA, 1-10 V dimmable (analog)
Article no. 17767010



Tender
LED converter 700 mA, 1-10 V dimmable (analog), white, Rectangular. Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz , Power: 20 W, Dimmable: Yes, Type of dimming: 1-10 V.

Article data	
Article no.	17767010
GTIN	4251433924104
Short description	LED converter 700 mA, 1-10 V dimmable (analog)
Material	Plastic
Colour	white
Shape	Rectangular
Length	110.5 mm
Width	52 mm
Hight	22 mm
Weight	0.102 kg
stamp	ENEC 05, EL
Conformance	CE


LED converter 700 mA, 1-10 V dimmable (analog)

Article no. 17767010

Operating technology of driver	
AC nominal voltage min	99 V
AC nominal voltage max	264 V
Frequency min	47 Hz
Frequency max	63 Hz
DC nominal voltage min	176 V
DC nominal voltage max	280 V
Protection class	II
Degree of protection	IP20
Power	2.1 W
Power max.	20 W
Output_ripple_current	3
Starting current	5 A, 50 µs
Suitable for emergency lighting	No
measure point (tc)	80 °C
Version	without
Power factor	0.95
max. no. lights on B16 A	50
Output voltage max	29.00 V
Output voltage min.	3.00 V
Flicker value Pst LM	1.00
Control	1-10 V
Number of poles	4
Environment temperature (ta)	-25 °C up to +50 °C
Measure point (tc)	max. +80 °C
Output current	700 mA
Safety devices against thermal overload	yes

Packing data	
Gross weight	0.121 kg
Length of packaging	60 mm
Packaging width	27 mm
Packaging height	150 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.