





LED converter 700 mA, DALI dimmable (digital)
Article no. 17788020



Tender
LED converter 700 mA, DALI dimmable (digital), white, Rectangular. Material: Plastic, Degree of protection: (DIN EN 60529) IP20, Protection class: (DIN EN 61140) II, Voltage: 230V AC 50Hz , Power: 38 W, Dimmable: Yes, Type of dimming: DALI-2/PUSH.

Article data	
Article no.	17788020
GTIN	4251433924371
Short description	LED converter 700 mA, DALI dimmable (digital)
Material	Plastic
Colour	white
Shape	Rectangular
Length	146.5 mm
Width	44 mm
Hight	30 mm
Scope of delivery	Plug&Play output cable, length 110 mm and connection box
Weight	0.198 kg
stamp	ENEC 05, EL
Conformance	CE, UKCA


LED converter 700 mA, DALI dimmable (digital)

Article no. 17788020

Operating technology of driver	
AC nominal voltage min	198 V
AC nominal voltage max	264 V
Frequency min	47 Hz
Frequency max	63 Hz
DC nominal voltage min	176 V
DC nominal voltage max	275 V
Protection class	II
Degree of protection	IP20
Power	7 W
Power max.	38 W
Output_ripple_current	3
Starting current	5 A, 50 µs
Suitable for emergency lighting	Yes
Ambient temperature	-25 up to 45 °C
measure point (tc)	85 °C
Version	Plug & Play + Connection Box
Power factor	0.95
Control	DALI-2/PUSH
Number of poles	4
Enviroment temprature (ta)	-25 °C bis +45 °C
Measure point (tc)	max. +85 °C
Output current up to	700 mA
Safety devices against thermal overload	yes

Packing data	
Gross weight	0.258 kg
Length of packaging	140 mm
Packaging width	110 mm
Packaging hight	120 mm
Disposal at end of life	This product must not be disposed of with household waste. You are obliged, to dispose of such electrical waste separately. By disposing of electrical waste and other old or defective electronics separately, you support recycling or other forms of re-use. In that way you help to take care and to avoid that harmful substances get into the environment.