

## Han 3A-agg-QB



Part number	09 20 003 0301	
Specification	Han 3A-agg-QB	
HARTING eCatalogue	https://b2b.harting.com/09200030301	
Identification		
Category	Hoods/Housings	
Series of hoods/housings Han A <sup>®</sup>		
Type of hood/housing	Bulkhead mounted housings	
Description of hood/ housing	Straight	

## Version

Locking type	Single locking lever
Size	3 A
Field of application	Standard Hoods/housings for industrial applications
Technical characteristics	
Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP44
	IP65 / IP67 with seal screw 09 20 000 9918
Material properties	
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

( 0,	
Material (seal)	NBR
Material (locking)	Steel
Surface (locking)	Zinc plated
RoHS	compliant with exemption
RoHS exemptions	$_{\rm 6a:}$ Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 $\%$ lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No

Page 1 / 2 | Creation date 2018-08-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties

REACH SVHC substances	Yes
REACH SVHC substances	Lead
Specifications and approvals	
Approvals	DNV GL
Commercial data	
Packaging size	10
Net weight	34.5 g
Country of origin	Germany
Customs tariff number	85389099