Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	LLLOAILD KLOOI	LATION (LO) 2019/2	ots with regard to energ	gy labelling of light	
Supplier's name	e or trade mark:	Böhmer-Leuchten			
Supplier's address: Böhmer-Leuchten, Lüttkewiesen 11, 59757 Müschede Arnsberg HSK, DE					
Model identifie	r: 44267				
Type of light so	urce:				
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS	
Light source cap-type (or other electric interface)		matt cover			
Mains or non-m	nains:	NMLS	Connected light source (CLS):	Nein	
Colour-tuneable	e light source:	Nein	Envelope:	-	
High luminance light source:		Nein			
Anti-glare shield	d:	Nein	Dimmable:	No	
Product parameters					
Parameter		Value	Parameter	Value	
		General product p		_	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		18	Energy efficiency class	F	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 450 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode pexpressed in W	oower (P _{on}),	18,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	225	Spectral power	See image	
dimensions	Width	225	distribution in the	in last page	
without	Depth	40		Seite 1 / 2	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	- -			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	80	Survival factor	0,95			
the lumen maintenance factor	0,95					

(a)'-': not applicable; (b)'-': not applicable;