Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			1013 With regard to energ	87
Supplier's name o	or trade mark:	Böhmer-Leuchten		
Supplier's address	s: Böhmer-Leu	chten, Lüttkewiese	n 11, 59757 Müschede A	rnsberg HSK, DE
Model identifier:	44269			
Type of light sour	ce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		matt cover		
(or other electric interface)				
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein
Colour-tuneable light source:		Nein	Envelope:	-
High luminance light source:		Nein		
Anti-glare shield:		Nein	Dimmable:	No
		Product para	imeters	
Parameter		Value	Parameter	Value
		General product		T
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		18	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 450 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P _{on}), expressed in W		18,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		<u>-</u>	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
	Height	735	Spectral power	See image
	Width	160	distribution in the	in last page
without	Depth	45		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	- -		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	80	Survival factor	0,95		
the lumen maintenance factor	0,95				

(a)'-': not applicable; (b)'-': not applicable;