Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	LEGATED REGOL	27111011 (20) 2013/2	OIS With regard to energ	by labelling of light		
Supplier's name	or trade mark:	Böhmer-Leuchten				
Supplier's address: Böhmer-Leuchten, Lüttkewiesen 11, 59757 Müschede Arnsberg HSK, DE						
Model identifier:	34128					
Type of light sou	rce:					
Lighting technology used:		LED	Non-directional or directional:	NDLS		
Light source cap-type (or other electric interface)		matt cover				
Mains or non-mains:		NMLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:		Nein	Envelope:	-		
High luminance light source:		Nein				
Anti-glare shield:		Nein	Dimmable:	No		
		Product para	meters	1		
Parameter		Value	Parameter	Value		
		General product	parameters:			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		12	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode power (P _{on}), expressed in W		12,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		<u>-</u>	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
	Height	60	Spectral power	See image		
	Width	90	distribution in the	in last page		
without	Depth	130				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	- -			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	80	Survival factor	0,95			
the lumen maintenance factor	0,95					

(a)'-': not applicable; (b)'-': not applicable;