## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	PELLOATED REGOT	-AITON (LO) 2013/2	.013 with regard to energ	gy labelling of light	
Supplier's name	e or trade mark:	Böhmer-Leuchten			
<b>Supplier's address:</b> Böhmer-Leuchten, Lüttkewiesen 11, 59757 Müschede Arnsberg HSK, DE					
Model identifie	er: 34220				
Type of light so	urce:				
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS	
Light source cap-type (or other electric interface)		matt cover			
Mains or non-m	· · · · · · · · · · · · · · · · · · ·	NMLS	Connected light source (CLS):	Nein	
Colour-tuneable	e light source:	Nein	Envelope:	-	
High luminance light source:		Nein			
Anti-glare shield	d:	Nein	Dimmable:	No	
Product parameters					
Parameter		Value	Parameter	Value	
		General product	parameters:		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	F	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		540 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P <sub>on</sub> ), expressed in W		6,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,50	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		<del>-</del>	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80	
Outer	Height	160	Spectral power	See image	
dimensions	Width	220	distribution in the	in last page	
without	Depth	50		Seite 1 /	

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	- -			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	80	Survival factor	0,95			
the lumen maintenance factor	0,95					

(a)'-': not applicable; (b)'-': not applicable;