## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: ESYLUX

Supplier's address: -

## Model identifier: EO10299001 A

## Type of light source:

| Lighting technology used:     | LED           | Non-directional or directional: | NDLS |  |  |
|-------------------------------|---------------|---------------------------------|------|--|--|
| Light source cap-type         | 30 - 40 V DC, |                                 |      |  |  |
| (or other electric interface) | 449 mA CC     |                                 |      |  |  |
| Mains or non-mains:           | NMLS          | Connected light source (CLS):   | Nein |  |  |
| Colour-tuneable light source: | Nein          | Envelope:                       | -    |  |  |
| High luminance light source:  | Nein          |                                 |      |  |  |
| Anti-glare shield:            | Nein          | Dimmable:                       | No   |  |  |
| Product parameters            |               |                                 |      |  |  |

|                                 |   | i iouuci para             | ineters   |              |  |  |
|---------------------------------|---|---------------------------|---|--------------|--|--|
| Parameter                       |   | Value                     | Parameter   | Value        |  |  |
| General product parameters:     |   |                           |   |              |  |  |
| 0,                              | mption in on-<br>200 h), rounded<br>est integer                               | 16                        | Energy efficiency<br>class  | F            |  |  |
| indicating if it in a sphere (3 | us flux (φuse),<br>refers to the flux<br>360º), in a wide<br>in a narrow cone | 1 750 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 3 000        |  |  |
| On-mode<br>expressed in W       | power (P <sub>on</sub> ),   | 16,0                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |
| for CLS, expre                  | ndby power (P <sub>net</sub> )<br>essed in W and<br>e second decimal          | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |
| Outer<br>dimensions<br>without  | Height  | 25                        | Spectral power  | See image    |  |  |
|                                 | Width   | 240                       | distribution in the   | in last page |  |  |
|                                 | Depth   | 240                       |   |              |  |  |
|                                 |   |                           |   | Seite        |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting |             | range 250 nm to 800<br>nm, at full-load |                |
|--|-------------|---|----------------|
| control parts,<br>if any<br>(millimetre)                                       |             |   |                |
| Claim of equivalent power <sup>(a)</sup>                                       | -           | lf yes, equivalent power (W)            | -              |
|  |             | Chromaticity<br>coordinates (x and y)   | 0,437<br>0,404 |
| Parameters for LED and OLED ligh   | nt sources: | · · ·                                   |                |
| R9 colour rendering index value  | -3          | Survival factor                         | -              |
| the lumen maintenance factor   | -           |   |                |
| (a), , , , , , , , , , , , , , , , , , ,                                       |             |   |                |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

