



Abbildung ähnlich

Product Features

Basic-line splice box, extensible, 19"/1U, 6xSC-D, OM3, aqua

- sheet steel housing, powder coated
- labelled ports
- with slide-in unit
- can be tilted downwards when opened
- front quick release (push-pull)
- splice cassette for holding 12 or 24 pigtails
- inserted crimp splice holder
- prepared with pigtails inserted in bundle of 12 incl. 6 x SC-D ceramic couplings
- 12 SC-fibre pigtails G50/125 µm, 2 m, MM PC, grade C
- with test protocol for all fibres incl. serial number
- mounted blind stops by less than 12 ports
- 2 x PG13,5/M20 - cable glands in the back (each 2 x right/left)
- 1 x PG13.5 gland in scope of delivery
- black (similar to RAL 9005)

Features**General**

| | |
|---------------------|----------------------------|
| Surface | steel sheet, powder-coated |
| Classification | OM3 |
| Protection class IP | 20 |
| Halogen Free | Yes |
| GTIN (EAN) | 4043921667033 |

Mounting types

| | |
|-------------------------------------|-----|
| (19-inch)-installation, 1 rack unit | Yes |
|-------------------------------------|-----|

Dimensions/Weights without packaging

| | |
|-----------|-----|
| Length mm | 482 |
| Width mm | 245 |
| Height mm | 44 |

Certifications

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|

References

| | |
|-------------|--|
| Accessories | 228040502, 228040602, 228040802, 228040902, 228060500, 228060600, 228060800, 228060900, 228070000, 228070100, 228070200, 228070312 |
|-------------|--|