## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Schiefer

Supplier's address: Schiefer Lighting, Potterbakkerstraat 35, 4871EP Etten-Leur, NL

## Model identifier: 145683814

## Type of light source:

| Lighting technology used:     | other | Non-directional or directional: | NDLS |  |  |
|-------------------------------|-------|---------------------------------|------|--|--|
| Light source cap-type         | E14   |                                 |      |  |  |
| (or other electric interface) |       |                                 |      |  |  |
| Mains or non-mains:           | MLS   | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No    | Envelope:                       | -    |  |  |
| High luminance light source:  | No    |                                 |      |  |  |
| Anti-glare shield:            | No    | Dimmable:                       | Yes  |  |  |
| Product parameters            |       |                                 |      |  |  |

| Parameter   |   | Value                  | Parameter  | Value        |  |  |
|---|---|------------------------|--|--------------|--|--|
| General product parameters:                       |   |                        |  |              |  |  |
| 0,  | nption in on-<br>00 h), rounded<br>st integer                                   | 15                     | Energy efficiency<br>class   | G            |  |  |
| dicating if it refe<br>a sphere (360°)            | s flux (φuse), in-<br>ers to the flux in<br>, in a wide cone<br>rrow cone (90º) | 70 in Sphere<br>(360°) | Correlated colour<br>temperature,<br>rounded to the near-<br>est 100 K, or the<br>range of correlat-<br>ed colour temper-<br>atures, rounded to<br>the nearest 100 K,<br>that can be set | 2 500        |  |  |
| On-mode pow<br>pressed in W                       | ver (P <sub>on</sub> ), ex-   | 15,0                   | Standby power (P <sub>sb</sub> ),<br>expressed in W and<br>rounded to the sec-<br>ond decimal  | 0,00         |  |  |
| (P <sub>net</sub> ) for CLS, e                    | andby power<br>expressed in W<br>the second dec-                                | -                      | Colour rendering in-<br>dex, rounded to the<br>nearest integer, or<br>the range of CRI-val-<br>ues that can be set   | 100          |  |  |
| Outer dimen-                                      | Height  | 57                     | Spectral power dis-  | See image    |  |  |
| sions without                                     | Width   | 26                     | tribution in the   | in last page |  |  |
| separate con-<br>trol gear, light-<br>ing control | Depth   | 26                     | range 250 nm to 800<br>nm, at full-load  | Dago 1 / 3   |  |  |

| parts and non-<br>lighting con-<br>trol parts, if<br>any (millime-<br>tre) |                    |   |                |
|--|--------------------|---|----------------|
| Claim of equivalent powe   | r <sup>(a)</sup> - | lf yes, equivalent power (W)            | -              |
|  |                    | Chromaticity coordi-<br>nates (x and y) | 0,450<br>0,414 |

(a)'-' : not applicable;

(b)'-' : not applicable;

