



Produkteigenschaften

| | |
|-------------------------------|--|
| Form | rund |
| Breite | mit Putzlaschen 105 mm |
| Tiefe | 46 mm |
| Bohrlochgröße | 82 mm |
| Einbauöffnung | 60 mm |
| Farbe | blau / orange |
| Gesamtanzahl der Einführungen | 2 x M20 4 x M25 |
| Einführungen von hinten | Kabel 2 x M12 |
| Zugentlastet | Nein |
| Anreihbar | Ja |
| Schraubdome | 4 |
| Aufnahme Deckenhaken | Nein |
| Schallschutz | in Kombination mit Thermoschaum (P717) bis 64 dB |
| Luftdicht | Ja |
| Wärmebrückenfrei | Ja, nur in Kombination mit Thermoschaum (P717) |
| Leistungsübergang | Vollisoliert |

Thermodose THD-45 - Die luftdichte Unterputzdose für sekundenschnelles Einschäumen - bye bye Gips!

- » Schnellmontage mit Thermoschaum
- » Wärmebrückenfreie Installation nach DIN 18015-5
- » Werkzeuglose Rohreinführung M20/M25
- » Absolut luftdicht
- » Schallschutz bis 64 dB
- » Membranrastzähne gleichen unebene Bohrlöcher aus
- » Integrierter Putzanschlag = putzbündige Installation
- » SCS-Verbindungstechnik = feste Verbindung und einfache Durchverdrahtung

| | |
|---------------|-----------------------|
| Serie | - |
| Artikelnummer | P774 |
| Kategorie | Unterputzinstallation |
| Montageart | Schaum |
| Einsatz | Unterputz |
| EAN | 4260182065020 |

Materialeigenschaften

| | |
|---------------------|-----|
| Material Gehäuse | PP |
| Material Einführung | TPE |



Thermo box THD-70 - The airtight flush-mounted box for foaming in seconds - bye bye plaster!

- » Quick installation with thermo foam
- » Installation without thermal bridges according to DIN 18015-5
- » Toolless conduit entry M20/M25
- » Absolutely airtight
- » Sound insulation up to 64 dB
- » Membrane ratchet teeth compensate for uneven drill holes
- » Integrated plaster stop = flush plaster installation
- » SCS connection technology = fixed connection and simple through-wiring

| | |
|----------------------|-----------------------------|
| Series | - |
| Article No. | P774 |
| Category | Flush mounting installation |
| Type of installation | Foam |
| Use | Flush mounting |
| EAN | 4260182065020 |

| | |
|----------------------------|-----|
| Material properties | |
| Material box | PP |
| Material insertion | TPE |

Product features

| | |
|---|--|
| Shape | round |
| Wide | with plaster lugs 105 mm |
| Depth | 46 mm |
| Hole size | 82 mm |
| Installation opening | 60 mm |
| Color | blue / orange |
| Total number of entries for conduit and cable | 2 x M20 4 x M25 |
| Entries from behind | Cable 2 x M12 |
| Strain relief | No |
| Bayable | Yes |
| Screw domes | 4 |
| Ceiling hook | No |
| Sound insulation | in combination with thermo foam (P717) up to 64 dB |
| Airtight | Yes |
| Thermal bridge-free | Yes, only in combination with thermo foam (P717) |
| Line transition | Fully insulated |